HKKT250A 1800V…SERIES

FEATURES

* International standard package

APPLICATIONS

* DC motor control
* Softstart AC motor controller
* Light, heat and temperature control

ADVANTAGES

* Space and weight savings
* Simple mounting with two screws
* Improved temperature and power cycling

Symbol	Test Conditions	Maximum Ratings	Unit
I_{TRMS}, I_{FRMS} I_{TAVM}, I_{FAVM}	$T_{VJ}=T_{VJM}$ $T_C=85^oC$; 180° sine	400 250	A
I_{TSM}, I_{FSM}	$T_{VJ}=45^oC$ t=10ms (50Hz), sine V_R=0 t=8.3ms (60Hz), sine	9200 10100	A
	$T_{VJ}=T_{VJM}$ t=10ms(50Hz), sine V_R=0 t=8.3ms(60Hz), sine	8000 8800	
i^2dt	$T_{VJ}=45^oC$ t=10ms (50Hz), sine V_R=0 t=8.3ms (60Hz), sine	423000 423000	A^2s
	$T_{VJ}=T_{VJM}$ t=10ms(50Hz), sine V_R=0 t=8.3ms(60Hz), sine	320000 321000	
$(di/dt)_{cr}$	$T_{VJ}=T_{VJM}$ repetitive, I_T=45A f=50Hz, t_p=200us $V_D=2/3V_{DRM}$ I_G=0.45A non repetitive, $I_T=I_{TAVM}$ di_G/dt=0.45A/us	130 500	A/us
$(dv/dt)_{cr}$	$T_{VJ}=T_{VJM}$; $V_{DR}=2/3V_{DRM}$ R_{GK}= ; method 1 (linear voltage rise)	1000	V/us
P_{GM}	$T_{VJ}=T_{VJM}$ t_p=30us $I_T=I_{TAVM}$ t_p=300us	120 60	W
P_{GAV}		20	W
V_{RGM}		10	V
T_{VJ} T_{VJM} T_{stg}		-40...+125 125 -40...+125	°C
V_{ISOL}	50/60Hz, RMS t=1min I_{ISOL}<1mA t=1s	3000 3600	V~
M_d	Mounting torque (M5) Terminal connection torque (M5)	2.5-4.0/22-35 2.5-4.0/22-35	Nm/lb.in.
Weight	Typical including screws	750	g

Symbol	Test Conditions	Maximum Ratings	Unit
IRRM, IDRM	TVJ=TVJM; VR=VRRM; VD=VDRM	70	mA
VT, VF	IT, IF=323A; TVJ=25oC	1.50	V
VTO	For power-loss calculations only (TVJ=125oC)	0.83	V
rT		0.85	mΩ
VGT	VD=6V; TVJ=25oC TVJ=-40oC	2.5 2.6	V
IGT	VD=6V; TVJ=25oC TVJ=-40oC	150 200	mA
VGD	TVJ=TVJM; VD=2/3VDRM	0.25	V
IGD		10	mA
IL	TVJ=25oC; tp=10us; VD=6V **IL** IG=0.45A; diG/dt=0.45A/us	300	mA
IH	TVJ=25oC; VD=6V; RGK=	150	mA
tgd	TVJ=25oC; VD=1/2VDRM IG=0.45A; diG/dt=0.45A/us	2	us
tq	TVJ=TVJM; IT=20A; tp=200us; -di/dt=10A/us typ. VR=100V; dv/dt=20V/us; VD=2/3VDRM	200	us
QS	TVJ=TVJM; IT, IF=25A; -di/dt=0.64A/us	760	uC
IRM		275	A
RthJC	per thyristor/diode; DC current per module	0.095 0.0645	K/W
RthJK	per thyristor/diode; DC current per module	0.169 0.0845	K/W
dS	Creeping distance on surface	12.7	mm
dA	Strike distance through air	9.6	mm
a	Maximum allowable acceleration	50	m/s2

Outline Table





Fig. 1 Surge overload current
I_{TSM}, I_{FSM}: Crest value, t: duration



Fig. 2 $\int i^2t$ versus time (1-10 ms)



Fig. 2a Maximum forward current
at case temperature



Fig. 3 Power dissipation versus on-state current and ambient temperature
(per thyristor or diode)



Fig. 4 Gate trigger characteristics



Fig. 5 Three phase rectifier bridge: Power dissipation versus direct output current
and ambient temperature



Fig. 6 Gate trigger delay time



Fig. 7 Three phase AC-controller: Power dissipation versus RMS output current and ambient temperature



Fig. 8 Transient thermal impedance junction to case (per thyristor or diode)

R_{thJC} for various conduction angles d:

d	R_{thJC} (K/W)
DC	0.129
180°C	0.131
120°C	0.131
60°C	0.132
30°C	0.132

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.0035	0.099
2	0.0165	0.168
3	0.1091	0.456



Fig. 9 Transient thermal impedance junction to heatsink (per thyristor or diode)

R_{thJK} for various conduction angles d:

d	R_{thJK} (K/W)
DC	0.169
180°C	0.171
120°C	0.172
60°C	0.172
30°C	0.173

Constants for Z_{thJK} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.0033	0.099
2	0.0159	0.168
3	0.1053	0.456
4	0.04	1.36