
SCT50N120


Silicon carbide Power MOSFET 1200 V, 65 A, 59 mΩ (typ., T_J=150 °C) in an HiP247™ package

Datasheet - production data



HiP247

Figure 1: Internal schematic diagram



Features

- Very tight variation of on-resistance vs. temperature
- Very high operating temperature capability (T_J = 200 °C)
- Very fast and robust intrinsic body diode
- Low capacitance

Applications

- Solar inverters, UPS
- Motor drives
- High voltage DC-DC converters
- Switch mode power supplies

Description

This silicon carbide Power MOSFET is produced exploiting the advanced, innovative properties of wide bandgap materials. This results in unsurpassed on-resistance per unit area and very good switching performance almost independent of temperature. The outstanding thermal properties of the SiC material allows designers to use an industry-standard outline with significantly improved thermal capability. These features render the device perfectly suitable for high-efficiency and high power density applications.

Table 1: Device summary

Order code	Marking	Package	Packaging
SCT50N120	SCT50N120	HiP247™	Tube

The device meets ECOPACK standards, an environmentally-friendly grade of products commonly referred to as “halogen-free”. See *Section 5: "Package information"*.

This is information on a product in full production.

www.st.com

Contents

1 Electrical ratings 3
2 Electrical characteristics 4
2.1 Electrical characteristics (curves) 5
3 Package information 9
3.1 HiP247™ package information 9
4 Revision history 11

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 25	V
I_D	Drain current (continuous) at T_C = 25 °C	65	A
I_D	Drain current (continuous) at T_C = 100 °C	50	A
I_{DM}(1)	Drain current (pulsed)	130	A
P_{TOT}	Total dissipation at T_C = 25 °C	318	W
T_{stg}	Storage temperature range	-55 to 200	°C
T_j	Operating junction temperature range		°C

Notes:

(1)Pulse width limited by safe operating area.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case max	0.55	°C/W
$R_{thj\text{-}amb}$	Thermal resistance junction-ambient max	40	°C/W

2 Electrical characteristics

(T_{CASE} = 25 °C unless otherwise specified).

Table 4: On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{DSS}	Zero gate voltage drain current	V_{DS} = 1200 V, V_{GS} = 0 V		1	100	µA
		V_{DS} = 1200 V, V_{GS} = 0 V, T_J = 200 °C		10		µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = -10 to 22 V			100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 1 mA	1.8	3.0		V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 20 V, I_D = 40 A		52	69	mΩ
		V_{GS} = 20 V, I_D = 40 A, T_J = 150 °C		59		mΩ
		V_{GS} = 20 V, I_D = 40 A, T_J = 200 °C		70		mΩ

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 400 V, f = 1 MHz, V_{GS} = 0 V	-	1900	-	pF
C_{oss}	Output capacitance		-	170	-	pF
C_{rss}	Reverse transfer capacitance		-	30	-	pF
Q_g	Total gate charge	V_{DD} = 800 V, I_D = 40 A, V_{GS} = 0 to 20 V	-	122	-	nC
Q_{gs}	Gate-source charge		-	19	-	nC
Q_{gd}	Gate-drain charge		-	35	-	nC
R_g	Gate input resistance	f=1 MHz open drain	-	1.9	-	Ω

Table 6: Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E_{on}	Turn-on switching energy	V_{DD} = 800 V, I_D = 40 A, R_G= 2.2 Ω, V_{GS} = -5 to 20 V	-	530	-	µJ
E_{off}	Turn-off switching energy		-	310	-	µJ
E_{on}	Turn-on switching energy	V_{DD} = 800 V, I_D = 40 A, R_G= 2.2 Ω, V_{GS} = -5 to 20 V, T_J= 150 °C	-	670	-	µJ
E_{off}	Turn-off switching energy		-	334	-	µJ

Table 7: Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min	Typ.	Max	Unit
V_{SD}	Diode forward voltage	I_F = 20 A, V_{GS} = -5 V	-	3.5	-	V
t_{rr}	Reverse recovery time	I_{SD} = 40 A, di/dt = 2000/ns, V_{DD} = 800 V	-	55		ns
Q_{rr}	Reverse recovery charge		-	230	-	nC
I_{RRM}	Reverse recovery current		-	14	-	A

2.1 Electrical characteristics (curves)

Figure 2: Safe operating area




Figure 3: Thermal impedance




Figure 4: Output characteristics (TJ= 25 °C)




Figure 5: Output characteristics (TJ= 150 °C)




Figure 6: Output characteristics (TJ= 200 °C)




Figure 7: Transfer characteristics




Figure 8: Power dissipation




Figure 9: Gate charge vs gate-source voltage




Figure 10: Capacitance variations




Figure 11: Switching energy vs. drain current




Figure 12: Switching energy vs. junction temperature




Figure 13: Normalized V(BR)DSS vs. temperature




Figure 14: Normalized gate threshold voltage vs. temperature




Figure 15: Normalized on-resistance vs. temperature




Figure 16: Body diode characteristics (TJ= -50 °C)




Figure 17: Body diode characteristics (TJ= 25 °C




Figure 18: Body diode characteristics (TJ= 150 °C)




Figure 19: 3rd quadrant characteristics (TJ= -50 °C)




Figure 20: 3rd quadrant characteristics (TJ= 25 °C)





Figure 21: 3rd quadrant characteristics (TJ= 150 °C)



3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: ***www.st.com***. ECOPACK® is an ST trademark.

3.1 HiP247™ package information

Figure 22: HiP247™ package outline




Table 8: HiP247™ package mechanical data

Dim.	mm.		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

4 Revision history

Table 9: Document revision history

Date	Revision	Changes
17-Jun-2015	1	First release
12-May-2016	2	Modified title. Modified: Table 2: "Absolute maximum ratings", Table 4: "On/off states", Table 5: "Dynamic", Table 6: "Switching energy (inductive load)", and Table 7: "Reverse SiC diode characteristics". Added: Section 4.1: "Electrical characteristics (curves)". Minor text changes.
23-Jun-2016	3	Document status promoted from preliminary to production data.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved